

Beyond agriculture - Exploring the application of the Thornthwaite Moisture Index to infrastructure and possibilities for climate change adaptation

Michelle Philp and Michael Taylor

October2012

100 years from now (Meyer, 2008, TRB, 2008, Commonwealth of Australia, 2010). However, adaptation of infrastructure is likely to only occur as structures reach the end of their design life, as such maintenance and operations impacts on existing infrastructure also need to be considered.

Climate change is a global problem with global impacts. However, climate change impacts will vary spatially and according to characteristics of transport infrastructure installed in each locality. As such a single design safety factor to take climate change into account may not be suitable for application by infrastructure designers and managers. However, an index that takes into account the climate of the locality could be combined into infrastructure design and maintenance calculations to allow the changing climate to be included. It is proposed that the Thornthwaite Moisture Index has the ability to fulfil this role. This paper investigates where the Thornthwaite Moisture Index is currently used with respect to infrastructure and how this could be applied to adapting infrastructure to climate change. A mathematical model of road pavement degradation, suitable for site planning purposes and including climate impacts represented by the TMI, is described in the paper. A small application of the model is also provided, which reveals some interesting effects for climate change scenarios.

Section 6 of the paper provides a consolidated list of the nomenclature used in the model, and should be used as the basic reference for the factors and variables employed in the equations of the mathematical model.

2. The Thornthwaite Moisture Index

As stated previously, the Thornthwaite Moisture Index (TMI) can be generally described as reflecting the aridity or humidity of the soil and climate, calculated from the collective effects of precipitation, evapotranspiration, soil water storage, moisture deficit and run off (Austroads, 2010)

Thornthwaite hypothesised that climate could not be described by a single meteorological observation, such as precipitation. He came to this conclusion after observing conflicting examples of ecological communities with the same annual precipitation, which northern Europe resulted in fertile forests but only supported sparse desert vegetation in Africa (Keim, 2010, Thornthwaite, 1948). This led him to consider the notion of effective precipitation and further the notion of potential evapotranspiration. As significant research he discovered that the actual evaporation

Or

$$I_h = \frac{P - E_p}{E_p} \quad (2)$$

where I_h and I_a are indices of humidity and aridity respectively, P is water surplus, E_p is water deficiency, and E_p is water need or potential evapotranspiration.

Thornthwaite used the index to describe various climate types according to the moisture index limits. The various climate classifications are listed in Table 1.

do it X dZ } OE v š Z Á] š [• o] u š š Ç % o • •] () š } } v •

A further simplification of the index was given by Gen (1972) which relates the Thornthwaite

$$I = \frac{P}{10} \left(\frac{1000}{P} \right)^{0.714286} \quad (3)$$

$$I = \frac{P}{10} \left(\frac{1000}{P} \right)^{0.714286} \quad (4)$$

$$I = \frac{P}{10} \left(\frac{1000}{P} \right)^{0.714286} \quad (5)$$

where $P_m(t)$

investigate the use of TMI in the estimation of potential soil suctions beneath surface covers. The review also discussed the works of Wright (1978) who used TMI to estimate the distance moisture penetrated under the edges of slabs, McKeen and Johnson (1990) who used TMI to estimate diffusion rates for moisture in unsaturated soils and therefore estimate the active zone depth, and Perera et al. (2004) where the TMI was used as a part of a model to predict conditions beneath pavements. Further from their findings this review has found additional applications in this field.

Carpenter et al. (1974) conducted a study on the environmental influences important in studying non load associated pavement cracking in west Texas, USA. The project was part of a comprehensive program to verify the environmental cracking mechanisms and recommend maintenance and construction measures to alleviate the problem. Several mechanisms independent of traffic loads were found to generate pavement cracking including reflection cracking, thermal cracking, selective adsorption of asphalt by porous aggregates, and moisture changes. The TMI was found to be related to the equilibrium suction level which develops in the subgrade along the centre of a pavement (Carpenter et al., 1974) further supporting Aitchison and Richards (1965) who found the state of moisture beneath a pavement to be very influential on pavement behaviour.

Jayatilaka and Lytton (1997) incorporate the TMI in their methodology for predicting the ability to predict the roughness in a given wheel path in pavements with or without vertical moisture barriers. The study developed alternative design procedures for determining the soil deformation likely to occur and for predicting the impact of the soil deformations on pavement performance by including provisions for environmental input parameters such as the TMI. This study has been applied with success to road pavement design and pavement in USA. This work was further refined and developed into the windows based GUI model WINPRESS (Lytton et al., 2005)

The climatic conditions were accounted for in the model using the TMI under the first five different climate types defined by Australian Standard AS2870 (Standards Australia, 2011) as shown in Table 2, adapted from ARRB (2011). Table 2 in this paper has been extended from the table in ARRB (2011) to include all parts of Australia, including the arid regions. The climate types defined in this table proposed by Thornthwaite (see Table 1).

Table 2 Australian climatic types adapted from the Australian Standard AS2870 climate classes (Standards Australia, 2011)

Climatic Type for Australia	Thornthwaite Moisture Index Value R
-----------------------------	-------------------------------------

of 20 to 40 years. Understanding what the effects of climate change would have on infrastructure over this time period would allow managers and operators to budget better and prepare suitable management plans for infrastructure

pavements, as described below. Overall pavement degradation is expressed in terms of the International Roughness Index (IRI), $R(t)$ (m/km) at time t , where $R(t)$ is given by

$$R(t) = R_0 + \Delta R(t) \quad (8)$$

in which R_0 is the initial roughness index of the pavement and $\Delta R(t)$ is the change in roughness over time t . The road will be considered to have reached the end of its service life when

$$R(t) = R_{max}$$

Thus determination of t_{max} , where

$$R(t) = R_{k-v}; L = \Delta R(t) \quad (9)$$

will indicate the time of failure of the pavement.

The overall roughness of a sealed pavement is made of considerations of rutting and surface cracking, which are affected by traffic load and climate, and this can be assessed in terms of changes in IRI. The following scenario planning model has been developed from that given by ~~Wang et al.~~ (2010).

$$\Delta R(t) = L \left\{ \alpha Z(t) + \beta r(t) + \gamma E(t) \right\} \quad (10)$$

in which $Z(t)$ represents the cumulative traffic load on the pavement, $\alpha(t)$ is the percentage of cumulative cracking (% total lane area, 100%) by year, $r(t)$ is the cumulative rutting deterioration for a sealed granular pavement by year, and $E(t)$ is an environmental/climatic term, given by the following equation.

$$E(t) = L \left\{ \delta + \epsilon t \right\} \quad (11)$$

In equation 11

$$\delta = L \left\{ \eta + \theta \left(\frac{M(t)}{M_0} \right) \right\} \quad (12)$$

where $M(t)$ is the value of the TMI in year

The impacts of traffic load on pavement condition are represented by the $Z(t)$ in equation (10).

54 L sãrxõ:P,
t F ş Bãrtu/ :P, Erãz • ça A

Solution of equation 9 using equations 23-29 provides a model of pavement life dependent on changes in traffic, maintenance and environmental variables over time. Note that the form of equation 28 is compatible with the equivalent expression in Austroads (2010).

4.3 Application of the model

Two applications of the model are provided. The first indicates the likely difference in road pavement degradation for a given pavement, traffic load and maintenance program, but where the pavement is located in different climate zones. The second application shows the modelled degradation for a road pavement at a location undergoing climate change over a 50 year period.

Figure 2 shows the model results for a given road pavement under a set traffic load but located in different climate zones (from those defined in Table 2): class iii temperate, class iv temperate, class v temperate, class i sub-tropical, class ii sub-tropical, class iii sub-tropical, class iv sub-tropical, class v sub-tropical, class i tropical, class ii tropical, class iii tropical, class iv tropical, class v tropical.

Figure 2 Modelled effects of climate conditions on pavement degradation same pavement design, traffic load and maintenance schedule in different climate zones

Figure 3 provides an example of the use of the model for a changing climate it compares the forecast degradation over 50 years of a road pavement under different climate scenarios, with all other variables (traffic load and maintenance schedules) remaining the same. Three scenarios are presented in this plot using the Australian climate classes in Table 2

- x ^ v OE } íU]v Á Z] Z š Z o] dry temperate (Australian TMI class) over the 50 year period
- x ^ v OE } íU]v Á Z] Z š Z o] u š Dry temperate (Australian TMI class) over the 50 year period
- x ^ v OE } íU]v Á Z] Z š Z o] Australian TMI class through the 50 year period

2 Seal life (years)
1 Nominal maximum size of seal aggregate (mm)

7. References

- AITCHISON, G. D. & RICHARDS, B. GA1965 A nationwide Study of Moisture Conditions in Pavement Subgrades Throughout Australia: Factors in Planning a Regional Study Moisture Variation in Pavement Subgrades Division of Soil Mechanics, CSIRO.
- ARRB 2011. Modelling the Marginal Cost of Road Wear. National Transport Commission Australia <http://www.ntc.gov.au/filemedia/Reports/ModellingTheMarginalCostMay2011.pdf>.
- AUSTROADS 2004 Impact of climate change on road infrastructure - AP43/04, Sydney, Austroads Incorporated.
- AUSTROADS 2009 Guide to Pavement Technology: Part 2 Pavement structural design AGPT02/09, Sydney, Austroads Incorporated.
- AUSTROADS 2010 Predicting Structural Deterioration of Pavements at a Network Level Interim Models AP T159/10, Sydney, Austroads Incorporated.
- BRYANT, J. T. & HAQUE, M. A. 2011. Performance and design of foundations on unsaturated expansive soil. ALONSO, E. & GENS, A. (eds) Unsaturated Soils London: Taylor & Francis.
- CARPENTER, S. H., LYTTON, R. L. & EPPS, J. A. 1974. Environmental factors related to road pavement design. Highway Research Board, vol. 54, pp. 1-12.

- MARTIN, T. C. & RAMSAY, E. 1996. Rural pavement improvement prediction due to rehabilitation ARRB Transport Research Report ARR 289, Vermont South, Victoria, ARRB Transport Research.
- MARTIN, T. C. & ROBERTS, J. D. 1998. Network level pavement life cycle costing modelling for asset management. 9th Road Engineering Association of Asia and Australia (REAAA) Conference, Wellington, New Zealand.
- MCKEEN, R. & JOHNSON, L. 1990. Climate controlled soil design parameters for mat foundations. *Journal of Geotechnical Engineering*, 116, 1073-1094.
- MEYER, M. 2006. Design standards for U.S. transportation infrastructure: the implications of climate change. In: Special Report 29 Transportation Research Board, Washington D.C, USA.
- MRQ. 2009. Pavement Design Manual. Queensland Department of Main Roads, Brisbane.
- NCHRP 2006. Falling weight deflectometer usage: a synthesis of highway performance. National Cooperative Highway Research Program Report 381. Transportation Research Board, Washington D.C.
- OLIVER, J. W. 2006. Adding risk to a model for reseal intervention due to binder ageing. Proceedings of the 22nd ARRB Conference, 2006 Canberra, Australia. ARRB Group, Vermont South, Vic.
- PALMER, W. 1965. Meteorological drought-US Weather Bureau Research Paper No. 45. Washington D.C.: US Department of Commerce.
- PERERA, Y., ZAPATA, C., HOUSTON, W. & HOUSTON, S. 2004. Long term moisture conditions under highway pavements. *Geotechnical Engineering for Transportation Projects: Proceedings of GEOTRANS 2004*, Special Publication 26.
- RUSSAM, J. & COLEMAN, K. 1961. The effect of climatic factors on subgrade moisture conditions. *Geotechnique*, 7, 22-28.
- STANDARDS AUSTRALIA 2011. Residential slabs and footings. Australian Standard AS 2870. Standards Australia, Sydney.
- TAYLOR, M.A.P. 2008. Vulnerability analysis of regional road networks. Proceedings of the 22nd ARRB Conference August 2008 Adelaide Australia ARRB Group, Vermont South Vic
- TAYLOR, M. A. P. & HILP, M. 2010. Adapting to climate change: implications for transport infrastructure, transport systems and travel behaviour. *Road and Transport Research*, 19, 69-82.
- THORNTON, C. W. 1931. The climates of North America according to a new classification. *Geographical Review*, 21, 633-655.
- THORNTON, C. W. 1933. The climates of the world. *Geographical Review*, 23, 433-440.
- THORNTON, C. W. 1948. An approach toward a rational classification of climates. *Geographical Review*, 38, 55-94.
- TRB 2008. Potential impacts of climate change on US transportation